

**Pompa Jinjing
Alphafire**

AF-PJ 2.5
GXH50



Mengusung mesin Honda GXH50, Pompa Jinjing Alphafire AF-PJ 2.5 GXH50 ini dapat menghasilkan maximum pressure 90 Psi dan Straight Stream Reach 30 meter. Waktu hisap mencapai 10.81 detik dan laju aliran (flow) 190 L/menit.

Pompa yang ringan dengan berat kurang lebih 9 kg ini adalah salah satu bagian penting dalam penanganan kebakaran hutan dan lahan. Sangat tepat digunakan di lokasi yang sulit dijangkau.

Keunggulan

- » Sangat mudah digunakan.
- » Bahan bakar irit.
- » Sudah uji lab Damkar, NFPA 1921 Standard for Fire Department Portable Pumping Units LHU No. 117 / TB.06.01.
- » Honda AE Matching Test No. HPPI/2022/2 No. HPPI/2024/23
- » Jaminan layanan purna jual.

Spesifikasi Produk



ENGINE

Merk / Model	Honda / GXH50
Engine type	4-stroke, overhead valve, single cylinder
Bore X Stroke	41.8 X 36.0 mm
Displacement	49.4 cm ³
Max horsepower	1.8 kW 2.5PS (2.5 HP)@7000rpm
Net power (SAE J1349)*	1.6 kW (2.1 HP) @7000 rpm
Max. Net torque (SAE J1349)*	2.7 Nm (0.28 kgf.m, 2.0 lb-ft)@4.500 rpm
Compression ratio	8.0:1
Starting system	Recoil starter
Cooling system	Force air
Carburetor	Float type
Ignition system	Transistorized magneto ignition
Lubrication system	Force splash
Governor System	Mechanical centrifugal
Air cleaner	Semi-dry type
Oil capacity	0.25 liter
Recommended Fuel	Unlead 86 octane or higher
Fuel tank capacity	0.77 liter
Fuel consumption (net power)	0.91 liter

Handle dengan bahan aluminium yang nyaman digenggam



Max pressure
90 Psi

*Shut off

Straight stream reach
30 meter

Laju aliran (flow)


190 L/menit (NFPA 1921)

Waktu hisap

10.81 detik (NFPA 1921)

Hose outlet
Adaptor machino 1.5"

Suction inlet
Drat BSP 1.5"



PUMP

Type	Single stage centrifugal, direct drive
Body & diffusers	Anodized resistant aluminium
Impeller	Anodized resistant aluminium
Pump shaft	Stainless steel
Pump seal	Heat resistant rotary mechanical seal

